

## HOUE

# LIGHT

LIGHT No.1 is a portable solar-powered outdoor lamp, featuring the high-quality aesthetics known from interior lighting. The appearance is characterized by an elegant, smooth surface and an appealing color palette. The design ensures discrete placement of the solar module, which becomes an integrated part of the lamp.

LIGHT No.1 has adjustable light intensity levels and can be positioned standing or hung using the integrated handle. The adaptable nature and quality make this lamp remarkable and allow for usage that suits many needs and preferences.

Repairability and durability are both taken into consideration in the design; hence, all components, including the battery, can be replaced effortlessly.

Size: Ø13 cm x H21 cm Weight: 1 kg

LIGHT No.1 is Red Dot Winner 2024 in the category: "Lighting design".



## HOUSING

Made from aluminum and coated with a smooth matte finish.





## HANDEL

SOLAR CHARGER When solar charging the indicator dots will light up for 4 sec. and show how much the battery is charged.



Portable lamp that can be positioned standing or hung using the integrated handle.

**ELECTRONIC UNIT** 

Casing of recycled plastic. Waterproof IP65. Solar and wireless charger built in.

## Press switch pin to turn ON-OFF / Adjust the brightness to suit your needs and mood

1st press: on 100% light 2nd press: change to 50% light 3rd press: change to 10% light Long press will switch off the light in any position. Battery indicator dots illuminate 4 sec. when switching on.



**BATTERY LIFE** 

At 100% light – 1 day battery time At 50% light – 2 days battery time At 10% light – 6 days battery time The lamp will power down to "bw" after 5h and switch off after 10h continuous use.

The indicated hours are based on temperatures exceeding 10 °C.

**GLASS DOME** 

The glass dome is crafted from recycled glass with a vertical pattern that reflects the light, creating a beautiful visual effect.



6 COLORS







HOUSING

Made from aluminum and coated



CHARGING PAD

Cord length 1,5m



0/4



P





BATTERY LIFE (8H-100H)







WATERPROFF

CE





### Power supply 100-240V AC 50-60 Hz 0,5A Input

Output Frequency band H-Field

Light type

Kelvin

Power

Wireless charger for the lamp enclosed

Wireless charger input voltage

USB-C 5V DC 3A 9 DC 2,22A 12V DC 1,67A 110,6 KHz to 146,8 KHz -20,29 dBµA/m @ 10 m

LED

2500K 1W / 95 lm

9V DC

The luminaires shall be supplied by an independent separated extraslow voltage (SELV) power source, which should be certified with standard EN 61347-2-13 (Class II, IP20 or higher, fail-safe, or short circuit proof, with suitable output ratings, and maximum output

voltage shall not exceed 60 VDC).

## MAINTENANCE

Use a soft cloth with lukewarm water. Avoid any kind of chemical detergents.

## REPAIR

The product can be disassembled, allowing for the replacement of technical components. For spare part information, please contact your HOUE point of sale or visit houe.com.

agent or similar qualified person.

The light source contained in this luminaire shall only be replaced by the manufacturer, service











